



## MECHANICAL PRODUCTS

### HYDRAULIC COMPRESSION HEAD - ACCEPTS EXISTING 60 TON U-TYPE DIES - MAX. CONNECTOR: APPROX. 60 mm

سوپرس هیدرولیکی  
۶۰ تن

Code	Specification	Size (mm)	Weight (kg)	Features	Remarks	Accessories
EP-60S	<p>Ram stroke: 38.5 mm Oil volume required: 330 cc</p> <p>Force at die face: 540 KN (60 short ton) at 68.5 Mpa (10,000 PSI) of oil pressure</p>	146×450 dia×H	22	<p>The EP-60S compression head was designed as a portable tool for installing compression sleeves and terminals for and maintenance work.</p> <p>It operates in any position and gives 540 KN of working force to accept commercial compression joints used for transmission construction.</p>	<p>Dies are sold separately.</p> <ul style="list-style-type: none"> <li>Accepts all dies used for Alcoa, 60 ton compressors</li> <li>Specify the manufacturer's die and connector numbers</li> <li>Portable and light weight</li> <li>Detachable ground stand as a standard accessory</li> <li>Large handle for easy carrying</li> <li>Single acting hydraulic pump required.</li> <li>The HPE-35A is recommended to operate the EP-60S.</li> </ul>	<p>Steel carrying case, Ground stand</p> <p>Option: Die adapter for 12 ton U-type dies</p>

